

TUF-TRAC® ACRYLIC LATEX CRACK FILLER

SERIES A259



PORT BYRON, IL 61275 • (309)523-2121
1-800-747-1084 FAX # 1-309-523-3912

DESCRIPTION

TUF-TRAC® ACRYLIC LATEX CRACK FILLER is an easy to use compound for patching cracks up to 1/2" on asphalt or concrete surfaces. Unlike concrete or epoxy based patchers, TUF-TRAC® ACRYLIC LATEX CRACK FILLER stays flexible and moves with minor expansion and contraction of joints.

TYPE: Acrylic
COLOR: Black
PACKAGING: 1 gallon cans

TYPICAL USES

For use in patching cracks up to 1/2" on asphalt tennis courts, driveways, parking lots and playgrounds.

LIMITATIONS

- Applying at temperatures below 45°F can interfere with adhesion as well as prolong drying and curing times
- TUF-TRAC® ACRYLIC CRACK FILLER is not recommended for cracks wider than 1/2". If cracks are wider than 1/2", we recommend sawcutting and applying SANIPRO PERM-EPOX™ AR. Trowel off flush with adjacent surface.

OUTSTANDING FEATURES/BENEFITS

- Excellent flexibility, even at sub-zero temperatures
- Excellent exterior durability
- Excellent adhesion to clean asphalt and concrete

COMPOSITION AND PHYSICAL PROPERTIES

Net Weight/Gallon	15.1 ± .2 lbs.	Water Immersion	Two week immersion: Softens
Solids	By weight: 82% + 2% By volume: 68% + 2%	Adhesion	Excellent
VOC	0.09 lbs/gallon	Cleanup	Soap and Water
PVC	57.0% + 2%	Theoretical Coverage	1/4" x 1/4" = 300 lin ft/gal 1/2" x 1/4" = 150 lin ft/gal 1/2" x 1/2" = 75 lin ft/gal
Low Temperature Flexibility	40°F - Pass 0°F - Pass	Drying Time (@ 70°F, 50% humidity adequate ventilation)	1/4" 6 hours 1/2" 24 hours Complete Cure 2 - 5 days
Resistance/High Temperature Creep	Excellent @ 120°F	Freeze/Thaw Stability	DO NOT FREEZE

NOTICE

Before using this product, read all warnings and safety information printed on the label, the Material Safety Data Sheet, and the Technical Information Guide.

SURFACE PREPARATION

Surface must be clean, dry and free of all dirt, sediment and loose coatings. Rake, blow and/or hose out cracks to remove accumulated sand, mud and weeds. Allow to dry thoroughly.

APPLICATION

Press or squeeze TUF-TRAC® ACRYLIC LATEX CRACK FILLER firmly into place with a putty knife, trowel or caulking gun. Finish off flush with adjacent surface. In hot weather, keep finishing tools wet. Allow to dry 24 hours before topcoating. DO NOT apply when rain is imminent. Protect from rain at least 3 hours after application.



IMPORTANT NOTICE TO BUYER / WARRANTY AND LIMITATIONS ON OUR LIABILITY

We warrant our products to be free of manufacturing defects, and that they meet our current published physical properties and specifications. All information and suggestions presented are rendered gratis and is accurate to the best of our knowledge. They are based on technical data which we believe to be reliable, and are intended for use by persons having skill and "know-how," at their own discretion and risk. Prior to use, customers are cautioned to determine the suitability of our products for any given application through their own testing. NO WARRANTY IS MADE, EXPRESS OR IMPLIED, REGARDING SUCH INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS OBTAINED FROM IT'S USE OR THAT OUR PRODUCT SHALL BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. SUCH STATEMENTS ARE NOT INTENDED TO SUGGEST INFRINGEMENT OF ANY PATENT. Since conditions of use of our products are beyond our control, all suggestions and statements are made without guarantee, warranty or other responsibility, express or implied, on our part. We assume no responsibility for results obtained, or damages incurred, from their use beyond replacing material proved to be defective or refunding the purchase price of such material at our option. Acceptance of delivery of our product means you have accepted the terms of this warranty, whether or not purchase orders or other documents state terms that vary from this warning. No seller is authorized to make any representations or warranty or assume any other liability on our behalf with any sales of our products. © 2/98 SANDSTROM PRODUCTS COMPANY 6/3/02