

print date : 04/24/19

A520-W97 (page 1 )

SECTION 1

manufacturer : SANDSTROM PRODUCTS COMPANY  
 address : 224 South Main Street  
 : Port Byron, IL 61275  
 : USA  
 telephone# : (309) 523-2121  
 emergency# : (800) 424-9300  
 : (703) 527-3887

mfg. code id : A520-W97 Revision level : 4-04/24/2019

trade name : SANCRYL 520 - FP WHITE

Recommended use of chemical: OEM PRODUCTS

Restrictions on use: Do not use where there is a potential for contact with food.

SECTION 2

HAZARD IDENTIFICATION



HAZARD CLASSIFICATION:

DANGER!

FLAMMABLE LIQUID: CATEGORY 3

SKIN IRRITANT: CATEGORY 2

ASPIRATION HAZARD: CATEGORY 1

MUTAGENICITY: CATEGORY 1

REPRODUCTIVE TOXICITY: CATEGORY 2

CARCINOGEN: CATEGORY 1

STOT SE: CATEGORY 3 (D/D)

HAZARD & PRECAUTIONARY STATEMENTS:

FLAMMABILITY

H226: FLAMMABLE LIQUID AND VAPOR. P210: KEEP AWAY FROM HEAT/ SPARKS/ OPEN FLAMES/ HOT SURFACES. -NO SMOKING. P233: KEEP CONTAINER TIGHTLY CLOSED. P240: GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT. P241: USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING EQUIPMENT. P242: USE ONLY NON-SPARKING TOOLS. P243: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE. P280: WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION. P303,P361,P353: IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER. P370,P378: IN CASE OF FIRE: USE MEDIA SPECIFIED IN SECTION V TO EXTINGUISH. P403,P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL. P501: DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATIONAL/ INTERNATIONAL REGULATIONS.

EYE CONTACT

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE IN CONTACT WITH EYES.

SKIN CONTACT

H315: CAUSES SKIN IRRITATION. P264: WASH HANDS AND EXPOSED BODY PARTS THOROUGHLY AFTER HANDLING. P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P302,P352: IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. P362: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE. P332,P313: IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ ATTENTION.

INHALATION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INHALATION.

INGESTION

\*\*\* SAFETY DATA SHEET \*\*\*

print date : 04/24/19

A520-W97 (page 2 )

H304: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. P301+P310: IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER OR DOCTOR/PHYSICIAN. P331: DO NOT INDUCE VOMITING. P405: STORE LOCKED UP. P501: DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATION AL/ INTERNATIONAL REGULATIONS.

HAZARDS NOT CLASSIFIED  
NO DATA AVAILABLE.

OTHER HEALTH EFFECTS

H340: MAY CAUSE GENETIC DEFECTS. H350: MAY CAUSE CANCER. H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. H336: MAY CAUSE DROWSINESS OR DIZZINESS. P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. P202: DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P261: AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPORS/ SPRAY. P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ ATTENTION. P304+P340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREA THING. P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P405: STORE LOCKED UP. P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P501: DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATION AL/ INTERNATIONAL REGULATIONS.

---

OTHER HAZARDS:

USE ONLY IN A WELL-VENTILATED AREA OR IN A HOOD WHERE NO FLAME OR OTHER IGNITION SOURCES ARE PRESENT.DO NOT USE PRODUCT IN FOOD-PROCESSING OR FOOD-HANDLING EQUIPMENT OR ON SURFACES THAT MAY CONTACT FOOD. DO NOT ALLOW PRODUCT TO CONTAMINATE FOODSTUFFS. DO NOT EAT,DRINK OR SMOKE WHEN USING PRODUCT. WASHHANDS THOROUGHLY AFTER HANDLING. DO NOT BREATHE VAPORS. WEAR SUITABLE EYE AND SKIN PROTECTION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM TEMPERATURE EXTREMES. IN CASE OF SPILL OR LEAK, REMOVE IGNITION SOURCES AND VENTILATE AREA.

---

SECTION 3

no.	component	CAS#	% by wt.	SARA	vapor pressure (mm Hg @ 20 C)	LEL (@ 25 C)
1	n-BUTYL ACETATE	123-86-4	40 - 45	NO	10.00	1.38 @ 38 C
2	SOLVENT NAPHTHA, LIGHT ALIPHATIC	64742-89-8	1 - 5	NO	119.00 @ 37 C	1.00
3	PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6	10 - 15	NO	3.70	1.50 @ 200 C

SECTION 4 FIRST AID MEASURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SEEK PROMPT MEDICAL ATTENTION.

SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED. CONTAMINATED LEATHER ARTICLES CANNOT BE DECONTAMINATED AND SHOULD BE DISPOSED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DO NOT INDUCE VOMITING. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. SINCE ASPIRATION INTO THE LUNGS CAN CAUSE VERY SERIOUS, PERMANENT DAMAGE, THE DECISION OF WHETHER TO INDUCE VOMITING OR NOT SHOULD BE MADE BY A PHYSICIAN. DANGER FROM LUNG ASPIRATION MUST BE WEIGHED AGAINST TOXICITY WHEN CONSIDERING EMPTYING THE STOMACH. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

>> COMPONENT 2 MAY CAUSE SEVERE, PERMANENT DAMAGE IF ASPIRATED AND VOMITING SHOULD NOT BE INDUCED.

SECTION 5 FIRE FIGHTING MEASURES

flammability classification - OSHA : FLAMMABLE LIQUID - CLASS IC  
 - DOT : FLAMMABLE LIQUID

EXTINGUISHING MEDIA

USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

WARNING. FLAMMABLE. CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT HELMET, FACE SHIELD, BUNKER COAT, GLOVES, RUBBER BOOTS, AND A POSITIVE PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES

LARGE SPILLS >> EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. SMALL SPILLS >> TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL.

SECTION 7 HANDLING AND STORAGE

FLAMMABILITY

H226: FLAMMABLE LIQUID AND VAPOR. P210: KEEP AWAY FROM HEAT/ SPARKS/ OPEN FLAMES/ HOT SURFACES. -NO SMOKING. P233: KEEP CONTAINER TIGHTLY CLOSED. P240: GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT. P241: USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING EQUIPMENT. P242: USE ONLY NON-SPARKING TOOLS. P243: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE. P280: WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION. P303,P361,P353: IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER. P370,P378: IN CASE OF FIRE: USE MEDIA SPECIFIED IN SECTION V TO EXTINGUISH. P403,P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL. P501: DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATIONAL/ INTERNATIONAL REGULATIONS.

SECTION 8 EMPLOYEE PROTECTION

RESPIRATORY PROTECTION

AVOID PROLONGED OR REPEATED BREATHING OF VAPORS/MIST. IF EXPOSURE EXCEEDS TLV USE A NIOSH-APPROVED POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR TO PREVENT OVER EXPOSURE.

PROTECTIVE CLOTHING

AVOID CONTACT WITH EYES. WEAR GOGGLES IF THERE IS A LIKELIHOOD OF CONTACT WITH EYES. DO NOT GET ON SKIN OR ON CLOTHING.

ADDITIONAL PROTECTIVE MEASURES

USE VENTILATION AS REQUIRED TO CONTROL VAPOR/DUST CONCENTRATIONS. EYE WASH POUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

SECTION 9 PHYSICAL PROPERTIES

% volatile by volume	: 75.14 +/- 2%	weight per gallon	: 9.21 +/- .2
% volatile by weight	: 59.91 +/- 2%	VOC as supplied is	5.5152 pounds per gallon.

PHYSICAL STATE	: LIQUID	FLAMMABILITY (SOLID, GAS)	: NOT AVAILABLE
COLOR	: (W) White	FLAMMABILITY/EXPLOSIVE LIMITS	: NOT AVAILABLE
ODOR	: STRONG SOLVENT	VAPOR PRESSURE	: NOT AVAILABLE
ODOR THRESHOLD	: NOT AVAILABLE	VAPOR DENSITY	: NOT AVAILABLE
pH	: N/A	RELATIVE DENSITY	: 1.1080
MELTING/FREEZING POINT	: NOT AVAILABLE	SOLUBILITY	: NOT AVAILABLE
INITIAL BOILING POINT	: NOT AVAILABLE	PARTITION COEFFICIENT	: NOT RELEVANT
BOILING RANGE	: NOT AVAILABLE	AUTO-IGNITION TEMPERATURE	: NOT AVAILABLE
EVAPORATION RANGE	: NOT AVAILABLE	DECOMPOSITION TEMPERATURE	: NOT AVAILABLE
		VISCOSITY (AT 77F)	: 22-27 sec,#2 ZAHN

flash point : 75 +/-2 degrees F. SETAFASH

SECTION 10

STABILITY AND REACTIVITY

STABILITY : STABLE

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID

BASED ON THE PRESENCE OF COMPONENTS 1, 2 AND 3 AVOID OXIDIZING MATERIALS. BASED ON THE PRESENCE OF COMPONENT 2 AVOID HEAT, SPARKS, AND FLAME

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION 11

TOXICOLOGICAL INFORMATION

no.	(OSHA) PEL/TWA	PEL/CEILING	PEL/STEL	skin
1	150 ppm	N/E	N/E	N/E
2	400 PPM	N/E	N/E	N/E
3	N/E	N/E	N/E	N/E

no.	(ACGIH) TLV/TWA	TLV/CEILING	TLV/STEL	skin
1	150 ppm	N/E	200 ppm	N/E
2	400 PPM	N/E	N/E	N/E
3	N/E	N/E	N/E	N/E

>> The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15 mg/m3 for total dust and 5 mg/m3 for the respirable fraction. ACGIH recommends a TLV/TWA of 10 mg/m3 for total dust.

>> (SKIN) absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact.  
(N/E = not established)

>> None of the components of this product are recognized as carcinogenic.

SECTION 12

ECOLOGICAL INFORMATION

CAS#	Component	Harmful to Aquatic Life	Not Harmful to Aquatic Life	May be Harmful to Aquatic
000123-86-4	n-BUTYL ACETATE	: N	: Y	: N
064742-89-8	SOLVENT NAPHTHA, LIGHT ALIPHATIC	: N	: Y	: N
000108-65-6	PROPYLENE GLYCOL METHYL ETHER ACETATE	: Y	: N	: Y

SECTION 13

DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

WASTE CHARACTERIZATIONS AND COMPLIANCE WITH APPLICABLE LAWS ARE THE SOLE RESPONSIBILITY OF THE END USER. ALL DISPOSAL PRACTICES USED FOR THIS PRODUCT AND ITS CONTAINER(S) MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. THE INFORMATION PRESENTED IN THIS SDS PERTAINS ONLY TO THE PRODUCT AS SHIPPED.

SECTION 14 TRANSPORTATION INFORMATION

Land Transport

USDOT

Proper shipping name: PAINT  
 NOS Components :  
 Hazard class: 3  
 ID-number: UN1263  
 Packing group: III  
 Aquatic Toxicity: YES

Sea Transport

IMDG

Proper shipping name: PAINT  
 NOS Components : 1-METHOXY-2-PROPANOL, ACETATE  
 Hazard class: 3  
 ID-number: UN1263  
 Packing group: III  
 Aquatic Toxicity: YES

Air Transport

IATA/ICAO

Proper shipping name: PAINT  
 NOS Components : 1-METHOXY-2-PROPANOL, ACETATE  
 Hazard class: 3  
 ID-number: UN1263  
 Packing group: III  
 Aquatic Toxicity: YES

SECTION 15 REGULATORY INFORMATION

CAS#	Component	US TSCA Inventory	Canada Domestic Substance List	EC	Philippines	Japan	Korea	China	Australia
000123-86-4	n-BUTYL ACETATE	: YES	: YES	EC	: YES				
						: YES	Korea		
								: YES	Australia
064742-89-8	SOLVENT NAPHTHA, LIGHT ALIPHATIC	: YES	: YES	EC	: YES				
						: UNKNOWN	Korea		
								: YES	Australia
000108-65-6	PROPYLENE GLYCOL METHYL ETHER ACETATE	: YES	: YES	EC	: YES				
						: YES	Korea		
						: UNKNOWN		: YES	Australia



**WARNING** This product can expose you to chemicals including QUARTZ ,which is known to the State of California to cause cancer, and TOLUENE ,which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

no.	component	CAS#	SARA
1	n-BUTYL ACETATE	123-86-4	NO
2	SOLVENT NAPHTHA, LIGHT ALIPHATIC	64742-89-8	NO
3	PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6	NO

SECTION 16 OTHER INFORMATION

- H M I S -

HEALTH	: 2
FLAMMABILITY	: 3
REACTIVITY	: 0
PERSONAL PROTECT.:	X

(X = ask your supervisor for specialized handling directions)

CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.