print date : 05/14/19 L278-B30 (page 1 )

SECTION 1

manufacturer : SANDSTROM PRODUCTS COMPANY

address : 224 South Main Street

: Port Byron, IL 61275

: USA

telephone# : (309) 523-2121

emergency# : (800) 424-9300 : (703) 527-3887

mfg. code id : L278-B30

trade name : HEAT RESISTANT COATING-DTM PRIMER

Recommended use of chemical: OEM PRODUCTS

Restrictions on use: Do not use where there is a potential for contact with food.

Revision level : 3-05/14/2019

\_\_\_\_\_\_

SECTION 2 HAZARD IDENTIFICATION



### HAZARD CLASSIFICATION:

\_\_\_\_\_\_\_

WARNING!

EYE IRRITANT: CATEGORY 2A SKIN IRRITANT: CATEGORY 2

STOT SE: CATEGORY 3 (RESPIRATORY)

HAZARD & PRECAUTIONARY STATEMENTS:

### FLAMMABILITY

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE WITH FLAMMABILITY.

### EYE CONTACT

H319: CAUSES SERIOUS EYE IRRITATION. P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P264: WASH HANDS AND EXPOSED BODY PARTS THOROUGHLY AFTER HANDLING. P305, P351, P338: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. P337, P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ ATTENTION.

### SKIN CONTACT

H315: CAUSES SKIN IRRITATION. P264: WASH HANDS AND EXPOSED BODY PARTS THOROUGHLY AFTER HANDLING. P280: WEAR PROTECTIVE GLOVES/
PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P302, P352: IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. P362: TAKE OFF
CONTAMINATED CLOTHING AND WASH BEFORE REUSE. P332, P313: IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ ATTENTION.

## INHALATION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INHALATION.

INGESTION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INGESTION.

HAZARDS NOT CLASSIFIED

NO DATA AVAILABLE.

OTHER HEALTH EFFECTS

#### \*\*\* SAFETY DATA SHEET \*\*\*

print date : 05/14/19 L278-B30 (page 2 )

H335: MAY CAUSE RESPIRATORY IRRITATION. P261: AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPORS/ SPRAY. P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. F304+F340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREA THING. P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P405: STORE LOCKED UP. P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P501: DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATION AL/ INTERNATIONAL REGULATIONS.

------

### OTHER HAZARDS:

USE ONLY IN A WELL-VENTILATED AREA OR IN A HOOD WHERE NO FLAME OR OTHER IGNITION SOURCES ARE PRESENT.DO NOT USE PRODUCT IN FOOD-PROCESSING OR FOOD-HANDLING EQUIPMENT OR ON SURFACES THAT MAY CONTACT FOOD. DO NOT ALLOW PRODUCT TO CONTAMINATE FOODSTUFFS. DO NOT EAT, DRINK OR SMOKE WHEN USING PRODUCT. WASHHANDS THOROUGHLY AFTER HANDLING. DO NOT BREATHE VAPORS. WEAR SUITABLE EYE AND SKIN PROTECTION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM TEMPERATURE EXTREMES. IN CASE OF SPILL OR LEAK, REMOVE IGNITION SOURCES AND VENTILATE AREA.

print date : 05/14/19 L278-B30 (page 3 )

SECTION 3

vapor pressure % by wt. CAS# SARA no. component (mm Hg @ 20 C) (@ 25 C) \_\_\_\_\_\_\_ 1312-76-1 15 - 20 POTASSIUM SILICATE NO N/A N/A IRON MANGANESE OXIDE BLACK 33 75864-23-2 5 - 10 YES N/A N/A (N/A = not applicable) 

SECTION 4 FIRST AID MEASURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF ANY SYMPTOMS PERSIST.

SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DO NOT INDUCE VOMITING. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. SINCE ASPIRATION INTO THE LUNGS CAN CAUSE VERY SERIOUS, PERMANENT DAMAGE, THE DECISION OF WHETHER TO INDUCE VOMITING OR NOT SHOULD BE MADE BY A PHYSICIAN. DANGER FROM LUNG ASPIRATION MUST BE WEIGHED AGAINST TOXICITY WHEN CONSIDERING EMPTYING THE STOMACH. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

SECTION 5

FIRE FIGHTING MEASURES

flammability classification - OSHA : NOT APPLICABLE

- DOT : NOT REGULATED

EXTINGUISHING MEDIA

NOT APPLICABLE

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

NOT APPLICABLE

UNUSUAL FIRE AND EXPLOSION HAZARDS

NOT APPLICABLE

SECTION 6

ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES

LARGE SPILLS >> EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. SMALL SPILLS >> TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL.

print date : 05/14/19 L278-B30 (page 4 )

SECTION 7
FLAMMABILITY

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE WITH FLAMMABILITY.

HANDLING AND STORAGE

SECTION 8 EMPLOYEE PROTECTION

RESPIRATORY PROTECTION

AVOID PROLONGED OR REPEATED BREATHING OF VAPORS/MIST. IF EXPOSURE EXCEEDS TLV USE A NIOSH-APPROVED POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR TO PREVENT OVER EXPOSURE.

PROTECTIVE CLOTHING

AVOID CONTACT WITH EYES. WEAR GOGGLES IF THERE IS A LIKELIHOOD OF CONTACT WITH EYES. DO NOT GET ON SKIN OR ON CLOTHING.

ADDITIONAL PROTECTIVE MEASURES

USE VENTILATION AS REQUIRED TO CONTROL VAPOR/DUST CONCENTRATIONS. EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

SECTION 9 PHYSICAL PROPERTIES

\_\_\_\_\_

% volatile by volume : 87.48 +/- 2%

% volatile by weight : 66.41 +/- 2%

PHYSICAL STATE : LIQUID FLAMMABILITY (SOLID, GAS: NOT AVAILABLE

COLOR : (B) Black FLAMMABILITY/EXPLOSIVE LIMITS: NOT AVAILABLE

ODOR : NONE VAPOR PRESSURE : NOT AVAILABLE

ODOR THRESHOLD : NOT AVAILABLE

VAPOR DENSITY : NOT AVAILABLE

ph : N/A RELATIVE DENSITY : 1.3157

MELTING/FREEZING POINT: NOT AVAILABLE SOLUBILITY: NOT AVAILABLE

INITIAL BOILING POINT: NOT AVAILABLE

BOILING RANGE: NOT AVAILABLE

EVAPORATION RANGE: NOT AVAILABLE

SOLUBILITY: NOT AVAILABLE

AUTO-IGNITION TEMPERATURE: NOT AVAILABLE

DECOMPOSITION TEMPERATURE: NOT AVAILABLE

VISCOSITY (AT 77F) : 15 - 20 sec, #2 ZAHN

: 10.97 +/- .2

flash point : NOT APPLICABLE

SECTION 10

STABILITY AND REACTIVITY

-----

STABILITY : STABLE

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR

weight per gallon

CONDITIONS AND MATERIALS TO AVOID

BASED ON THE PRESENCE OF COMPONENT 1 AVOID STRONG ACIDS. BASED ON THE PRESENCE OF COMPONENT 1 AVOID LEAD, COPPER, AND THEIR ALLOYS. BASED ON THE PRESENCE OF COMPONENT 1 AVOID CONTACT WITH ZINC.

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

# \*\*\* SAFETY DATA SHEET \*\*\*

	*** SAFETY DATA SHEET *	***	
print date : 05/14/19			30 (page 5 )
SECTION 11	TOXICOLOGICAL INFORMATION		
no. (OSHA) PEL/TWA	PEL/CEILING	PEL/STEL	skin
1 N/E	N/E	n/e	N/E
2 N/E	N/E	N/E	N/E
no. (ACGIH) TLV/TWA	TLV/CEILING	TLV/STEL	skin
1 N/E	n/e	N/E	N/E
2 N/E	N/E	N/E	N/E
>> The dried film of this pro	oduct may become a dust nuisance when removed b	y sanding or grinding. OSHA recommen	ds a PEL/TWA of 15
mg/m3 for total dust and 5 mg	g/m3 for the respirable fraction. ACGIH recomme	ends a TLV/TWA of 10 mg/m3 for total	dust.
	tribute to the overall exposure to this materia		
(enzi), deperperent may con-			not established)
		= 21/11)	not established)
>> None of the components of	this product are recognized as carcinogenic.		
_			.======================================
SECTION 12	ECOLOGICAL INFORMATION	N	
CAS# Compone	ent		
001312-76-1 POTASS	IUM SILICATE		
Harmful to Aquatic Life : N	Not Harmful to Aquatic Life: N	May be Harmful to Aquatic: Y	
	ANGANEGE OVERE BURGE 22		
	ANGANESE OXIDE BLACK 33  Not Harmful to Aquatic Life: Y	day be Harmful to Aguatic. N	
	Not nathral to Aquatic bile: 1		
SECTION 13	DISPOSAL CONSIDERATION	NS	
WASHE DISPOSAL			·
WASTE DISPOSAL			
	COMPLIANCE WITH APPLICABLE LAWS ARE THE SOLE RE		
USED FOR THIS PRODUCT AND ITS	S CONTAINER(S) MUST BE IN COMPLIANCE WITH ALL I	FEDERAL, STATE AND LOCAL LAWS AND REG	GULATIONS. THE
INFORMATION PRESENTED IN THIS	S SDS PERTAINS ONLY TO THE PRODUCT AS SHIPPED.		
SECTION 14	TRANSPORTATION INFORM	MATION	
Land Transport			
_			
USDOT			
Proper chipping same: ITM	TMPD OILANMINV		
- <del>"</del>	ITED QUANTITY		
NOS Components :			
Hazard class:			
ID-number:			
Packing group: II			
Aquatic Toxicity: YES			

print date : 05/14/19 L278-B30 (page 6 )

Sea Transport

IMDG

Proper shipping name: CORROSIVE LIQ BASIC INORGANIC NOS

NOS Components : SILICIC ACID, POTASSIUM SALT

Hazard class:

ID-number: Packing group: UN3266

Aquatic Toxicity:

II YES

Air Transport

IATA/ICAO

Proper shipping name: CORROSIVE LIQ BASIC INORGANIC NOS

NOS Components : SILICIC ACID, POTASSIUM SALT

Hazard class:

8

ID-number:

UN3266

Packing group:

II

Aquatic Toxicity:

YES

SECTION 15 REGULATORY INFORMATION 

CAS# Component 001312-76-1 POTASSIUM SILICATE EC : YES

Korea

: YES

: UNKNOWN

US TSCA Inventory

: UNKNOWN Japan : YES

Philippines

China : UNKNOWN Australia : YES

075864-23-2 IRON MANGANESE OXIDE BLACK 33

US TSCA Inventory : YES Canada Domestic Substance List : YES EC : YES

Philippines : YES Japan : UNKNOWN Korea China : UNKNOWN Australia : YES

print date : 05/14/19 L278-B30 (page 7 )

SECTION 15 REGULATORY INFORMATION CONTINUED

WARNING This product can expose you to QUARTZ , which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov \_\_\_\_\_\_ CAS# \_\_\_\_\_\_\_ POTASSIUM SILICATE 1312-76-1 IRON MANGANESE OXIDE BLACK 33 75864-23-2 YES Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the Section 313 List (40 CFR Part 372.65) are identified under the heading 'SARA 313'. \_\_\_\_\_\_ SECTION 16 OTHER INFORMATION - H M I S -HEALTH FLAMMABILITY : 0 REACTIVITY : 0 PERSONAL PROTECT.: X (X = ask your supervisor for specialized handling directions) CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES.

\_\_\_\_\_\_

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

------