



TUF-TRAC® LINE STRIPING
LINE STRIPE COATING: AIR DRY
SERIES A256
FOR SURFACES COATED WITH TUF-TRAC®

SANDSTROM
PRODUCTS COMPANY
 PORT BYRON, IL 61275 • 1-309-523-2121
 1-800-747-1084 • FAX: 1-309-523-3912
www.sandstromproducts.com

DESCRIPTION

Tuf-Trac® Line Striping is specially formulated for surfaces with Tuf-Trac®. It is compatible with other coating systems, as well as asphalt and conditioned concrete. Tuf-Trac® Line Striping creates sharp, bright lines that will not fade or peel, and its heavy body helps prevent "feathering" under the tape during application.

OUTSTANDING FEATURES/BENEFITS

- Textured for a slip-resistant finish
- Resistant to extreme weather conditions
- Resistant to cracking

TYPICAL USES

Designed for line striping tennis courts, playgrounds and parking lots that have been coated with Tuf-Trac® skid-resistant coating.

NOTICE

Before using this product, read all warnings, limitations and safety information printed on the product label, Safety Data Sheet (MSDS), and Technical Data Sheet.

LIMITATIONS

- Applying at temperatures below 50°F will greatly prolong drying time.
- Protect from rain for at least 2 hours after application.
- **DO NOT FREEZE.** If frozen, move to a warm place until thawed. Check sample can for homogeneous viscosity. If paint has gelled or is too thick to apply, discard.

GENERAL

Tennis courts should be striped according to U.S.L.T.A. Regulations.

COMPOSITION AND PHYSICAL PROPERTIES			
Net Weight per gallon	11.0 – 12.0 lbs.	Vehicle	Acrylic
Weight Solids	50.0 – 60.0%	Color	White
Volume Solids	35 - 38% (Theoretical)	Color Stability	Exterior: Excellent Interior: Excellent
VOC - Water	< 0.4 lbs./gallon		
Odor	Mild Solvent	Finish	Textured
Viscosity	80 ± 5 KU's @ 77°F	Gloss	Flat
Shelf Life	2 years DOM in unopened container	Cleanup	See CLEANUP
Storage Conditions	50°F – 100°F	Thinner	See THINNING
Freeze/Thaw Stability	KEEP FROM FREEZING	Drying Time:	@77°F±5°F and ≤ 70% relative humidity; adequate ventilation
Flash Point	Not flammable		
Coverage Rate	See COVERAGE	Tack Free	30 min. – 1 hour
Recommended Coats	1	Between Coats	1 – 2 hours
		Complete Cure	24 hours

COVERAGE

One gallon of Tuf-Trac® Line Striping covers 1200 lineal feet at a 2 inch width at 3.0 mils dry. Coverage rates listed are approximate. Actual rates will vary depending on method of application. Actual figures do not include spray loss. Also allow for surface irregularities and porosity, as well as material loss when mixing.

SURFACE PREPARATION

Allow Tuf-Trac® to dry at least 8 hours before applying Tuf-Trac® Line Striping. The surface must be thoroughly clean and dry.

STIRRING

IMPORTANT! This coating contains heavy pigments that settle during storage. Therefore, it should be stirred thoroughly before use.

THINNING

Thin sparingly with water, if needed.

APPLICATION

Tuf-Trac® Line Striping may be applied with a brush or roller. Spray application is not recommended.

CLEANUP

Clean equipment with water **before Tuf-Trac® Line Striping has dried.**

LIMITED WARRANTY

Tuf-Trac® Line Striping is warranted to be free of defects in workmanship and, when applied according to label instructions, will provide a coating for a period of 1 year from the date of application. If Tuf-Trac® Line Striping fails to perform, a claim must be initiated through the local supplier of the product. Upon determination of failure, material needed to correct the condition will be provided at no charge.

This warranty does not include shipping costs, labor or the cost of labor for the application or repair of the coating.

(SEE ADDITIONAL WARRANTY INFORMATION BELOW.)

IMPORTANT NOTICE TO BUYER / WARRANTY AND LIMITATIONS ON OUR LIABILITY

We warrant our products to be free of manufacturing defects and that they meet our current published physical properties and specifications. All information and suggestions presented are rendered gratis and are accurate to the best of our knowledge. They are based on technical data we believe to be reliable and are intended for use by persons having skill and "know-how" at their own discretion and risk. Prior to use, customers are cautioned to determine the suitability of our products for any given application through their own testing. **NO WARRANTY IS MADE, EXPRESS OR IMPLIED, REGARDING SUCH INFORMATION, THE DATA ON WHICH IT IS BASED OR THE RESULTS OBTAINED FROM ITS USE OR THAT OUR PRODUCT SHALL BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. SUCH STATEMENTS ARE NOT INTENDED TO SUGGEST INFRINGEMENT OF ANY PATENT.** Since conditions of use of our products are beyond our control, all suggestions and statements are made without guarantee, warranty or other responsibility, express or implied, on our part. We assume no responsibility for results obtained, or damages incurred, from their use beyond replacing material proved to be defective or refunding the purchase price of such material at our option. Acceptance of delivery of our product means you have accepted the terms of this warranty, whether or not purchase orders or other documents state terms that vary from this warning. No seller is authorized to make any representations or warranty or assume any other liability on our behalf with any sales of our products. SANDSTROM PRODUCTS COMPANY