print date : 11/06/20 u200-c01 (page 1 )

\_\_\_\_\_\_

SECTION 1

manufacturer : SANDSTROM PRODUCTS COMPANY

address : 224 South Main Street

: Port Byron, IL 61275

: USA

telephone# : (309) 523-2121 emergency# : (800) 424-9300

: (703) 527-3887

mfg. code id : u200-c01 Revision level : 0-8/25/2020

trade name : GLAZON SD UV ACRYLATE
Recommended use of chemical: ACRYLATE

Restrictions on use: Do not use where there is a potential for contact with food.

SECTION 2 HAZARD IDENTIFICATION



### HAZARD CLASSIFICATION:

WARNING!

EYE IRRITANT: CATEGORY 2A

SKIN SENSITIZER: CATEGORY 1

SKIN IRRITANT: CATEGORY 2

STOT SE: CATEGORY 3 (RESP)

# HAZARD & PRECAUTIONARY STATEMENTS:

# FLAMMABILITY

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE WITH FLAMMABILITY.

## EYE CONTACT

H319: CAUSES SERIOUS EYE IRRITATION. P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P264: WASH HANDS AND EXPOSED BODY PARTS THOROUGHLY AFTER HANDLING. P305, P351, P338: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. P337, P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ ATTENTION.

## SKIN CONTACT

H315: CAUSES SKIN IRRITATION. H317: MAY CAUSE AN ALLERGIC SKIN REACTION. P264: WASH HANDS AND EXPOSED BODY PARTS THOROUGHLY AFTER HANDLING. P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P261: AVOID BREATHING DUST/ FUME/GAS/ MIST/ VAPOR/ SPRAY. P272: CONTAMINATED WORK CLOTHING MUST NOT BE ALLOWED OUT OF THE WORKPLACE. P302, P352: IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. P362: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE. P363: WASH CONTAMINATED CLOTHING BEFORE REUSE. P333, P313: IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION. P501: DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATIONAL/ INTERNATIONAL REGULATIONS.

## INHALATION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INHALATION.

# INGESTION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INGESTION.

HAZARDS NOT CLASSIFIED

print date : 11/06/20 NO DATA AVAILABLE. u200-c01 (page 2 )

#### OTHER HEALTH EFFECTS

H335: MAY CAUSE RESPIRATORY IRRITATION. P261: AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPORS/ SPRAY. P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. P304+P340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREA THING. P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P405: STORE LOCKED UP. P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P501: DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATION AL/ INTERNATIONAL REGULATIONS.

------

### OTHER HAZARDS:

USE ONLY IN A WELL-VENTILATED AREA OR IN A HOOD WHERE NO FLAME OR OTHER IGNITION SOURCES ARE PRESENT.DO NOT USE PRODUCT IN FOOD-PROCESSING OR FOOD-HANDLING EQUIPMENT OR ON SURFACES THAT MAY CONTACT FOOD. DO NOT ALLOW PRODUCT TO CONTAMINATE FOODSTUFFS. DO NOT EAT, DRINK OR SMOKE WHEN USING PRODUCT. WASHHANDS THOROUGHLY AFTER HANDLING. DO NOT BREATHE VAPORS. WEAR SUITABLE EYE AND SKIN PROTECTION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM TEMPERATURE EXTREMES. IN CASE OF SPILL OR LEAK, REMOVE IGNITION SOURCES AND VENTILATE AREA.

print date : 11/06/20 u200-c01 (page 3 )

SECTION 3

					vapor pressure	LEL
no.	component	CAS#	% by wt.	SARA	(mm Hg @ 20 C)	(@ 25 C)
1	PROPYLIDNETRIMETHANOL, ETHOXYLATED ESTE	28961-43-5	50 - 55	NO	N/A	N/A
2	ACRYLATE ESTER MONOMER	42978-66-5	5 - 10	NO	.01	N/A
3	BENZENEACETIC ACID ESTER	442536-99-4	5 - 10	NO	N/A	N/A
					(N/A = not	applicable)

SECTION 4 FIRST AID MEASURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF ANY SYMPTOMS PERSIST.

SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED. CONTAMINATED LEATHER ARTICLES CANNOT BE DECONTAMINATED AND SHOULD BE DISPOSED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DO NOT INDUCE VOMITING. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. SINCE ASPIRATION INTO THE LUNGS CAN CAUSE VERY SERIOUS, PERMANENT DAMAGE, THE DECISION OF WHETHER TO INDUCE VOMITING OR NOT SHOULD BE MADE BY A PHYSICIAN. DANGER FROM LUNG ASPIRATION MUST BE WEIGHED AGAINST TOXICITY WHEN CONSIDERING EMPTYING THE STOMACH. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

SECTION 5

FIRE FIGHTING MEASURES -----

 ${\tt flammability\ classification\ -\ OSHA\ :\ NOT\ APPLICABLE}$ - DOT : NOT REGULATED

EXTINGUISHING MEDIA

NOT APPLICABLE

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS NOT APPLICABLE

UNUSUAL FIRE AND EXPLOSION HAZARDS NOT APPLICABLE

.....

print date : 11/06/20 u200-c01 (page 4 )

\_\_\_\_\_\_

ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES

LARGE SPILLS >> EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. SMALL SPILLS >> TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY

SECTION 7

HANDLING AND STORAGE

FLAMMABILITY

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE WITH FLAMMABILITY.

SECTION 8

EMPLOYEE PROTECTION

RESPIRATORY PROTECTION

AVOID PROLONGED OR REPEATED BREATHING OF VAPORS/MIST. IF EXPOSURE EXCEEDS TLV USE A NIOSH-APPROVED POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR TO PREVENT OVER EXPOSURE.

PROTECTIVE CLOTHING

AVOID CONTACT WITH EYES. WEAR GOGGLES IF THERE IS A LIKELIHOOD OF CONTACT WITH EYES. DO NOT GET ON SKIN OR ON CLOTHING.

ADDITIONAL PROTECTIVE MEASURES

USE VENTILATION AS REQUIRED TO CONTROL VAPOR/DUST CONCENTRATIONS. EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

SECTION 9 PHYSICAL PROPERTIES

% volatile by volume : not applicable

% volatile by weight : not applicable

PHYSICAL STATE : LIOUID FLAMMABILITY (SOLID, GAS: NOT AVAILABLE FLAMMABILITY/EXPLOSIVE LIMITS: NOT AVAILABLE COLOR : (C) Clear

ODOR : ACRYLATE VAPOR PRESSURE : NOT AVAILABLE ODOR THRESHOLD : NOT AVAILABLE VAPOR DENSITY : NOT AVAILABLE

RELATIVE DENSITY

MELTING/FREEZING POINT: NOT AVAILABLE SOLUBILITY : NOT AVAILABLE INITIAL BOILING POINT : NOT AVAILABLE PARTITION COEFFICIENT : NOT RELEVANT

BOILING RANGE : NOT AVAILABLE AUTO-IGNITION TEMPERATURE: NOT AVAILABLE EVAPORATION RANGE : NOT AVAILABLE DECOMPOSITION TEMPERATURE : NOT AVAILABLE

VISCOSITY (AT 77F) : 800-1200CPS,#4 @ 100

flash point : NOT APPLICABLE

------

SECTION 10

STABILITY AND REACTIVITY

STABILITY : STABLE

HAZARDOUS POLYMERIZATION : MAY OCCUR

weight per gallon : 9.26 +/- .2

: 1.10

CONDITIONS AND MATERIALS TO AVOID

BASED ON THE PRESENCE OF COMPONENT 2 AVOID OXIDIZING MATERIALS. BASED ON THE PRESENCE OF COMPONENT 1 AVOID STRONG ACIDS. BASED ON THE PRESENCE OF COMPONENT 1 AVOID STRONG ALKALIES. BASED ON THE PRESENCE OF COMPONENT 1 AVOID AMINES AND ALKANOLAMINES. BASED ON THE PRESENCE OF COMPONENT 2 AVOID LEAD, COPPER, AND THEIR ALLOYS.

print date : 11/06/20 u200-c01 (page 5 )

### HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION 11 TOXICOLOGICAL INFORMATION (OSHA) PEL/TWA PEL/CEILING PEL/STEL skin N/E no. (ACGIH) TLV/TWA TLV/CETLING TLV/STEL N/E N/E N/E N/E N/E N/E N/E N/E N/E >> The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15 mg/m3 for total dust and 5 mg/m3 for the respirable fraction. ACGIH recommends a TLV/TWA of 10 mg/m3 for total dust. >> (SKIN) absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact. >> None of the components of this product are recognized as carcinogenic. ECOLOGICAL INFORMATION Component -----028961-43-5 PROPYLIDNETRIMETHANOL, ETHOXYLATED ESTE Not Harmful to Aquatic Life: Y Harmful to Aquatic Life : N May be Harmful to Aquatic: N 042978-66-5 ACRYLATE ESTER MONOMER Harmful to Aquatic Life : N Not Harmful to Aquatic Life: Y May be Harmful to Aquatic: N ------442536-99-4 BENZENEACETIC ACID ESTER Harmful to Aquatic Life : N Not Harmful to Aquatic Life: N May be Harmful to Aquatic: Y ------SECTION 13 DISPOSAL CONSIDERATIONS WASTE DISPOSAL WASTE CHARACTERIZATIONS AND COMPLIANCE WITH APPLICABLE LAWS ARE THE SOLE RESPONSIBILITY OF THE END USER. ALL DISPOSAL PRACTICES USED FOR THIS PRODUCT AND ITS CONTAINER(S) MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. THE INFORMATION PRESENTED IN THIS SDS PERTAINS ONLY TO THE PRODUCT AS SHIPPED. SECTION 14 TRANSPORTATION INFORMATION Land Transport USDOT PAINT, NOI Proper shipping name: NOS Components Hazard class: ID-number: Packing group:

Aquatic Toxicity: YES

\*\*\* SAFETY DATA SHEET \*\*\* print date : 11/06/20 u200-c01 (page 6 ) Sea Transport IMDG Proper shipping name: ENVIROMENTALLY HAZ SUBSTANCE NOS NOS Components : METHYL BENZOYLFORMATE Hazard class: ID-number: UN3082 Packing group: III Aquatic Toxicity: Air Transport IATA/ICAO Proper shipping name: ENVIROMENTALLY HAZ SUBSTANCE NOS NOS Components : METHYL BENZOYLFORMATE Hazard class: ID-number: UN3082 III Packing group: Aquatic Toxicity: SECTION 15 REGULATORY INFORMATION Component CAS# 028961-43-5 PROPYLIDNETRIMETHANOL, ETHOXYLATED ESTE Canada Domestic Substance List : YES US TSCA Inventory : YES EC : YES Philippines Japan : YES : YES Korea : YES China : YES Australia : YES -----042978-66-5 ACRYLATE ESTER MONOMER US TSCA Inventory : YES Canada Domestic Substance List : YES EC : YES Philippines : YES : YES Japan Korea : YES China : YES Australia : YES 442536-99-4 BENZENEACETIC ACID ESTER US TSCA Inventory : YES Canada Domestic Substance List : YES EC : UNKNOWN : UNKNOWN Japan Philippines : UNKNOWN : UNKNOWN Korea China : UNKNOWN Australia : UNKNOWN no. component CAS# SARA PROPYLIDNETRIMETHANOL, ETHOXYLATED ESTE

28961-43-5

42978-66-5

442536-99-4

NO

NO

1

ACRYLATE ESTER MONOMER

BENZENEACETIC ACID ESTER

		OIL BIT DILLI DILBI	
print date	: : 11/06/20		u200-c01 (page 7 )
SECTION 16		OTHER INFORMATION	
	- H M I S -		
	HEALTH : 2     FLAMMABILITY : 1     REACTIVITY : 0     PERSONAL PROTECT : X    (X = ask your supervisor fo	r specialized handling directions)	
	CAN CONTAIN HAZARDOUS PROD	UCT RESIDUES EVEN WHEN EMPTY. WASH WITH SOAP AND WATER BEFORE EAT	'ING, DRINKING, SMOKING,
NO WA	RRANTY, EXPRESSED OR IMPLIE	IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAIN LITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.	•